

**Declaration of Performance**

**UK CONSTRUCTION PRODUCTS  
(AMENDMENT ETC) (EU EXIT)  
REGULATIONS 2020**

**No. 47458700**

1. Unique identification code of the product-type:

**Briton 5720.60 Cylinder Sashlock, Briton 5730.60 Bathroom Lock, Briton 5440.60 Mortice Latch,  
Briton 5750.60 Mortice Night Latch and Briton 5760.60 Escape Lock.**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the UK CPR:

**Briton 5720.60 Cylinder Sashlock, Briton 5730.60 Bathroom Lock, Briton 5440.60 Mortice Latch,  
Briton 5750.60 Mortice Night Latch and Briton 5760.60 Escape Lock.**

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in UK CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

**EN 12209: 2003 /AC 2005  
Notified testing laboratory No.1121 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 1121-CPR-UK- AG7921**

8. UK Technical Assessment:

**N/A**

9. Declared performance


Essential characteristics	Performance	Designated technical specification
Self closing 5.4.2 Closing force	Grade 8, ≤ 200 Kg door mass, 15 N maximum closing force	EN 12209: 2003 /AC 2005
5.1.2 Re-latching force of latch bolt	>2.5N	
Durability of self closing 5.3.1 Durability of latch action	Grade X, ≤ 200,000 test cycles, 120N side load on latch bolt.	
Ability to maintain the door in the closed		

position and not contribute to its spread of fire	Grade 1	
Control of Dangerous substances	<p>If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested:</p> <p>Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)</p>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:

Chris Crampton  
Controller - Unitary EMEIA, Finance and Accounting



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

30<sup>th</sup> March 2022